



## How to Order Commercial 5015 Reverse Bayonet (Front Release Crimp Contacts)

SPI4406A14S-2PFX-XX/X

**SPI Number** |

**Neoprene Inserts**

- 4400 = Wall Mount Receptacle
- 4401 = Cable Mount Receptacle
- 4402A = Box Mount Receptacle (Unthreaded Back)
- 4406 = Cable Plug
- 4408 = 90° Cable Plug\*

**UL Approved Silicone Inserts**

- 4500 = Wall Mount Receptacle
- 4501 = Cable Mount Receptacle
- 4502A = Box Mount Receptacle (Unthreaded Back)
- 4506 = Cable Plug
- 4508 = 90° Cable Plug\*

**Class** |

- A = General Duty Thread (Standard)
- S = Threaded Body, no General Duty Threaded  
(Does not apply to 4408 or 4508)

Leave Blank for the SPI4402A and SPI4502A

**Shell Size** |

10SL, 14S, 16S, 16, 18, 20, 22, 24, 28, 32, 36, 40

\* Only available in shell sizes 18, 20, 22, 24, 28, 32

**Insert Arrangement** |

Refer to Insert Arrangement Chart

**Deviations**

**Plating Options (RoHS)**

- = Dark Green Electrophoresis  
(Non-Conductive) (Standard Leave Blank)

**07** = Electroless Nickel (Conductive)

**Alternate Insert Positions**

- = Normal (Standard Leave Blank)
- W** = Alternate Position
- X** = Alternate Position
- Y** = Alternate Position
- Z** = Alternate Position

**First Mate/Last Break (FMLB)**

- = Standard Leave Blank
- F** = FMLB (Call For Information On  
Insert Arrangements and Contact  
Location)

**Contact Style**

- P** = Pin
- S** = Socket

Order Contacts Separately. See  
Contact Ordering Information