



## How to Order Commercial 5015 Reverse Bayonet (Front Release Crimp Contacts)

S-MS4406A14S-2PX-XX/X

**SPI Number** |

**Neoprene Inserts**

- 4400 = Wall Mount Receptacle
- 4401 = Cable Mount Receptacle
- 4402A = Box Mount Receptacle (Unthreaded Back)
- 4406 = Cable Plug
- 4408 = 90° Cable Plug\*

**UL Approved Silicone Inserts**

- 4500 = Wall Mount Receptacle
- 4501 = Cable Mount Receptacle
- 4502A = Box Mount Receptacle (Unthreaded Back)
- 4506 = Cable Plug
- 4508 = 90° Cable Plug\*

**Class** |

- A = General Duty Thread (Standard)
- S = Threaded Body, no General Duty Threaded  
(Does not apply to 4408 or 4508)
- Z = Modified

Leave Blank for the 4402A and 4502A

**Shell Size** |

10S, 10SL, 14S, 16S, 16, 18, 20, 22, 24, 28, 32, 36, 40

\* Only available in shell sizes 18, 20, 22, 24, 28, 32

**Deviations**

**Plating Options (RoHS)**

- Blank = Dark Green Electrophoresis  
(Non-Conductive)
- 06 = Zinc Black (Conductive)
- 07 = Electroless Nickel (Conductive)

**Alternate Insert Positions**

- = Normal (Standard Leave Blank)
- W = Alternate Position
- X = Alternate Position
- Y = Alternate Position
- Z = Alternate Position

**Contact Style**

- P = Pin
- S = Socket

Order Contacts Separately. See  
Contact Ordering Information

**Insert Arrangement**

Refer to Insert Arrangement Chart