



How to Order Commercial 5015 Reverse Bayonet (Solder Cup Contacts)

SPI4106A14S-2PAFX-XX/X

SPI Number

Neoprene Inserts

- 4100 = Wall Mount Receptacle
- 4101 = Cable Mount Receptacle
- 4102A = Box Mount Receptacle (Unthreaded Back)
- 4106 = Cable Plug
- 4108 = 90° Cable Plug*

UL Approved Silicone Inserts

- 4200 = Wall Mount Receptacle
- 4201 = Cable Mount Receptacle
- 4202A = Box Mount Receptacle (Unthreaded Back)
- 4206 = Cable Plug
- 4208 = 90° Cable Plug*

Class

- A = General Duty Thread (Standard)
- S = Threaded Body, no General Duty Threaded
(Does not apply to 4108 or 4208)

Leave Blank for the SPI4102A and SPI4202A

Shell Size

10SL, 14S, 16S, 16, 18, 20, 22, 24, 28, 32, 36, 40

* Only available in shell sizes 18, 20, 22, 24, 28, 32

Insert Arrangement

Refer to Insert Arrangement Chart

Deviations

Plating Options (RoHS)

= Dark Green Electrophoresis
(Non-Conductive) (Standard Leave Blank)

07 = Electroless Nickel (Conductive)

Alternate Insert Positions

= Normal (Standard Leave Blank)

W = Alternate Position

X = Alternate Position

Y = Alternate Position

Z = Alternate Position

First Mate/Last Break (FMLB)

= Standard Leave Blank

F = FMLB (Call For Information On Insert Arrangements and Contact Location)

Contact Adhesion

= Glued (Standard Leave Blank)

A = Not Glued

Contact Style

P = Pin (Silver Plated)

S = Socket (Silver Plated)*

PG = Pin (Gold Plated)

SG = Socket (Gold Plated)*

* Standard Style in #8 & #4 Sizes is Netsok