



How to Order Commercial 5015 Reverse Bayonet (Solder Cup Contacts)

S-MS4106A14S-2PAFX-XX/X

SPI Number

Neoprene Inserts

- 4100 = Wall Mount Receptacle
- 4101 = Cable Mount Receptacle
- 4102A = Box Mount Receptacle (Unthreaded Back)
- 4106 = Cable Plug
- 4108 = 90° Cable Plug*

UL Approved Silicone Inserts

- 4200 = Wall Mount Receptacle
- 4201 = Cable Mount Receptacle
- 4202A = Box Mount Receptacle (Unthreaded Back)
- 4206 = Cable Plug
- 4208 = 90° Cable Plug*

Class

- A = General Duty Thread (Standard)
- S = Threaded Body, no General Duty Threaded
(Does not apply to 4108 or 4208)
- Z = Modified

Leave Blank for the 4102A and 4202A

Shell Size

10S, 10SL, 14S, 16S, 16, 18, 20, 22, 24, 28, 32, 36, 40

* Only available in shell sizes 18, 20, 22, 24, 28, 32

Insert Arrangement

Refer to Insert Arrangement Chart

Deviations

Plating Options (RoHS)

- Blank = Dark Green Electrophoresis
(Non-Conductive)
- 06 = Zinc Black (Conductive)
- 07 = Electroless Nickel (Conductive)

Alternate Insert Positions

- = Normal (Standard Leave Blank)
- W = Alternate Position
- X = Alternate Position
- Y = Alternate Position
- Z = Alternate Position

First Mate/Last Break (FMLB)

- Blank = Standard
- F = FMLB (Style A)
- L = FMLB (Style B)

See Attached Pages For Styles

Contact Adhesion

- Blank = Glued
- A = Not Glued

Contact Style

- P = Pin (Silver Plated)
- S = Socket (Silver Plated)*
- PG = Pin (Gold Plated)
- SG = Socket (Gold Plated)*

* Standard Style in #8 & #4 Sizes is Netsok