



How to Order Commercial 5015 Series I (Solder Cup Contacts)

SPI3106A14S-2PAFX-XX/X

SPI Number

Neoprene Inserts

- 3100 = Wall Mount Receptacle
- 3101 = Cable Mount Receptacle
- 3102A = Box Mount Receptacle (Unthreaded Back)
- 3106 = Cable Plug
- 3108 = 90° Cable Plug*

UL Approved Silicone Inserts

- 3200 = Wall Mount Receptacle
- 3201 = Cable Mount Receptacle
- 3202A = Box Mount Receptacle (Unthreaded Back)
- 3206 = Cable Plug
- 3208 = 90° Cable Plug*

Class

- A = General Duty Thread (Standard)
- S = Threaded Body, no General Duty Threaded
(Does not apply to 3108 or 3208)

Shell Size

10S, 10SL, 14S, 16S, 16, 18, 20, 22, 24, 28, 32, 36, 40

* Only available in shell sizes 18, 20, 22, 24, 28, 32

Insert Arrangement

Refer to Insert Arrangement Chart

Deviations

Plating Options (RoHS)

= Dark Green Electrophoresis
(Non-Conductive) (Standard Leave Blank)

07 = Electroless Nickel (Conductive)

Alternate Insert Positions

= Normal (Standard Leave Blank)

W = Alternate Position

X = Alternate Position

Y = Alternate Position

Z = Alternate Position

First Mate/Last Break (FMLB)

= Standard Leave Blank

F = FMLB (Call For Information On Insert Arrangements and Contact Location)

Contact Adhesion

= Glued (Standard Leave Blank)

A = Not Glued

Contact Style

P = Pin (Silver Plated)

S = Socket (Silver Plated)*

PG = Pin (Gold Plated)

SG = Socket (Gold Plated)*

* Standard Style in #8 & #4 Sizes is Netsok