

SPECIFICATIONS:


Cable Range: 2.039"–2.328" (51.79–59.13)

Salt Spray: 500 Hours

Cable Pull Out Strength: 250 Lbs for 1 Hour

MIL-DTL-22992 QPL Qualified

REVISIONS LIST				
REV	ECO #	DESCRIPTION	DATE	APV'D
A		Initial Release		



NOTES:

All Measurements Are In Inches (mm)

No.	Name	Material/Finish	Remarks
1	Wire	304 Stainless Steel	1X7X1.25mm
2	Ring	304 Stainless Steel	

UNLESS NOTED TOLERANCES ARE: .X ± 0.15 (0.38) .XX ± 0.10 (0.25) ANGLES ± 1°	THIRD ANGLE PROJECTION 	 1170 S. PATTON ST. XENIA, OHIO 45385 PH: (937) 374-2700 FX: (937) 374-2717
--	----------------------------	---

UNIT: In (mm)	DRWN: RLM	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF SPT AND SHALL NOT BE COPIED, USED OR RE-PRODUCED WITHOUT PERMISSION.	TITLE Class L Cord Grip	
SCALE: NTS	DATE: 12/14/09		S P I P / N : MS90561-17	
	CHK'D: RLM		REV: A	
SHEET: 1 OF 1	APV'D: RLM		CUSTOMER P/N:	