



How to Order Commercial 26482 High Density Solder

SPI16A12-10P-XX/X

SPI Number |

12E = Box Mount Receptacle (Unthreaded Back)

16 = Cable Plug

Class |

A = General Duty Threaded

J = Water Tight Gland Seal with Strain Relief

P = Environmental Potting

S = Threaded Body with no Grommet or Back Shell*

U = No Grommet with Back Nut

V = No Grommet with Strain Relief

W = Water Tight Gland Seal without Strain Relief

Z = Modified

Leave Blank for the SPI12E

* See Back shell ordering for available back shells

Note: SPI cannot guarantee the compatibility of
Another manufacturer's back shell on an
SPI connector

Shell Size |

8, 10, 12, 14

Insert Arrangement |

Refer to Insert Arrangement Chart

Deviations

Plating Options

= Cadmium Olive Drab (Non-RoHS,
Conductive) (Standard Leave Blank)

02 = Zinc Cobalt Green (Non-RoHS,
Conductive) (5000 Piece Minimum)

03 = Zinc Cobalt Black (Non-RoHS,
Conductive) (5000 Piece Minimum)

05 = Zinc Green (RoHS, Conductive)

06 = Zinc Black (RoHS, Conductive)

07 = Electroless Nickel (RoHS,
Conductive)

08 = Soft Anodized Black (RoHS,
Non-Conductive)

09 = Hard Anodized Black (RoHS,
Non-Conductive)

Contact Style

P = Pin

S = Socket

P1 = Pin Straight PCB

S1 = Socket Straight PCB